

Flat flexible cable for Electric Vehicle Charging infrastructure.

BASED TO: IEC 60502-1



E_{ca}

APPLICATION

Flat flexible cable for EVC infrastructure in parkings. For residential or corporate electric vehicle charging installations. The flat cable system allows you a hassle-free installation & easy expansion, all along the installed length of the cable. The electrician simply connects the new charging stations to the existing infrastructure.

- EVC (Electric Vehicle Charging).

CONSTRUCTION

Conductor

Electrolytic annealed copper, class 5 (flexible) according to EN 60228 and IEC 60228.

Insulation

PVC insulation type PVC/A according to IEC 60502-1.

Assembly of cores

The cores are parallel in only one layer, forming a flat cable.

Colours and position are the following:

brown + blue + green/yellow + black + grey.

Outer sheath

PVC outer sheath type ST2 according to IEC 60502-1, grey colour.

COMPATIBILITY

Cable compatible with all major flat connection modules.

CHARACTERISTICS



Electrical performance

Nominal voltage: 0,6/1 kV.



Thermal performance

Maximum conductor temperature: 70 °C.

Minimum service temperature: -40°C (fixed and protected installations).

Maximum short-circuit temperature: 160 °C (maximum 5 s.).



Fire performance

Flame non-propagation according to IEC 60332-1 / EN 60332-1.

Reaction to fire CPR: E_{ca} according to EN 50575.



Mechanical performance

Minimum bending radius: 5 x smaller dimension.

Impact resistance: AG2 Medium severity.



Environmental performance

Chemical & Oil resistance: Acceptable.

Water resistance: AD5 Jets.




Installation conditions

Open Air.

On cable trays.

Wall mounted.



STANDARDS / COMPLIANCE



Based to

IEC 60502-1



Standards and approvals

RoHS / CE



CPR (Construction Products Regulation)

E_{ca}

